



Main

Range of product	OptiLine 45 OptiLine 70
Cabling installation system	Trunking
Product type	Cable shelf
Colour	White (RAL 9010)
Quantity package 1 / unit	24 m

Complementary

Trunking material	Plastic Aluminium
Trunking dimension	75 x 55 mm 120 x 55 mm 165 x 55 mm 95 x 55 mm 155 x 55 mm 140 x 55 mm 185 x 55 mm 80 x 55 mm
Fixing mode	Snap-fitted
Product material	PVC (polyvinyl chloride)
Length	1000 mm
Height	17 mm
Width	47 mm

Environment

Standards	73/23/EEC 93/68/EEC EN 50085-1:2005 EN 50085-1:2013/A1 EN 50085-2-1:2006 EN 50085-2-1:2011/A1 NF C 68-102
Operating temperature	-25...60 °C
IP degree of protection	IP30

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	170 g
Package 1 Height	0.2 cm
Package 1 width	4.7 cm
Package 1 Length	100 cm

Offer Sustainability

EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile

Contractual warranty

Warranty	18 months
----------	-----------