



Main

Range	Resi9
Product name	Resi9 MP
Product or component type	Enclosure
Enclosure type	Modular enclosure
Nb of 18 mm modules per row	8
Nb of horizontal rows	1
Type of door	Translucid
Width	196 mm outside:
Height	198 mm outside:
Depth	101.5 mm outside:

Complementary

Enclosure mounting	Surface
9 mm pitches	16
Total number of 18 mm modules	8
[In] rated current	63 A
Type of rail	35 mm asymmetrical rail
Mounting plate description	Without mounting plate
Cable entry	1 bare flange 1 trunking flange
Terminal block function	Without
Enclosure material	Back part: technoplastic Door: technoplastic Front face: technoplastic
Internal depth	80 mm
Colour	Front face: white (RAL 9003)

	Door: translucid
Market segment	Residential

Environment

Standards	IEC 60439-3 IEC 60695-2-11 EN 50102 IEC 60670-24 IEC 529
Quality labels	IMQ
Fire resistance	Door: 650 °C Back part: 650 °C Front face: 650 °C
IP degree of protection	IP40
IK degree of protection	IK07
Ambient air temperature for operation	-25...60 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	520 g
Package 1 Height	10.2 cm
Package 1 width	19.6 cm
Package 1 Length	22.8 cm
Unit Type of Package 2	BB1
Number of Units in Package 2	10
Package 2 Weight	5.3 kg
Package 2 Height	30 cm
Package 2 width	52 cm
Package 2 Length	40 cm
Unit Type of Package 3	P12
Number of Units in Package 3	160
Package 3 Weight	96.8 kg
Package 3 Height	120 cm
Package 3 width	80 cm
Package 3 Length	120 cm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	Product Environmental Profile
Halogen content performance	Halogen free product

Contractual warranty

Warranty	18 months
----------	-----------